

Neelnox

10752 Deerwood Park Blvd S, Waterview II, Ste#100
Jacksonville, Florida 32256 Tel: 904 880 5557 Fax: 904 302 7757
Email: info@neelnoxmosaics.com Web: www.neelnoxmosaics.com

Y I S H E L F : SERIES 300 INSTALLATION INSTRUCTIONS

Product Features

- Equipped with SoundDefy™ noise concealing technology
- Premium 304 Grade Stainless Steel
- Sloped Bottom*
- Hand Crafted
- Hardware included for a complete installation

Tools You'll Need



Congratulations On Your Purchase

“Quality is
not an act,
it is a habit.”
-Aristotle

Congratulations on purchasing the finest. Quality has been a habit at Neelnox since the very first day of its inception in 1963 and it is a habit that has strengthened with time. We hope that you are completely satisfied with your new product. Prior to installation please take a few moments to review the guidelines listed here. Should you have any questions or concerns, or if you'd like to share just how happy you are with the product, please feel free to contact us at info@neelnoxmosaics.com.

Installation

- Determine the location where you would like to install the Series 300 Y I SHELF™.
- Place the shelf at the desired location on the substrate and mark along the outer edges of the shelf which are in contact with the wall.
- Place the template along the markings and make new ones for the holes along the perforations.
- Drill a 15/64" diameter hole on these markings. Insert the plastic anchors supplied along with the screws.
- Prepare the included Y I BOND™ by mixing the resin and hardener in equal parts.
- Spread the prepared Y I BOND™ resin and hardener along the edges of the shelf which will be in contact with the wall after installation.
- Slide in the Series 300 Y I SHELF™ along the horizontal profile on the screws on one wall and push to the perpendicular wall till the shelf rests on the screws. Place weight over the shelf (approx. 4 lbs) and secure the shelf with tape.
- Remove weights and tape after a period of 8 hours. The Y I BOND™ cures fully after a period of 24 hours. Use silicone caulk along the edges to waterproof.

Care & Maintenance

- Neelnox recommends 3M Stainless steel cleaners or a damp soft cloth, mild dishwashing soap and a non-abrasive sponge if required. Always clean along the direction of the grain. Do not use acid or corrosive solutions, chloride solutions, abrasive pads or steel wool for cleaning.